

Tuborg Advanced AGM

Model	Napięcie [V]	Pojemność [Ah]	Prąd rozruchu [A]	Wymiary [mm]			Polaryzacja
				Dł.	Szer.	Wys.	
TX 9H	12	9	160	150	87	105	1
TX 12H	12	12	220	152	88	131	1
TX 14H	12	14	240	150	87	145	1
TX 14HL	12	14	240	150	87	161	0
TX 20HL	12	20	340	175	87	155	0
TX 24HL	12	24	380	175	87	155	0
TX 32HL	12	32	480	175	87	175	0
TB 14H	12	14	260	134	89	164	1
TB 14HL	12	14	260	134	89	164	0

Tuborg GEL

Model	Napięcie [V]	Pojemność [Ah]	Prąd rozruchu [A]	Wymiary [mm]			Polaryzacja
				Dł.	Szer.	Wys.	
YTX4L-GEL	12	4	60	114	71	86	0
YTX5L-GEL	12	5	100	114	71	106	0
YTX7A-GEL	12	7	120	151	88	94	1
YTX7L-GEL	12	7	110	114	71	131	0
YTX9-GEL	12	8,4	150	151	88	106	1
YTX10S-GEL	12	9,1	200	150	87	93	1
YTX12-GEL	12	10,5	200	152	88	131	1
YT12B-GEL	12	12	220	150	71	131	1
YTX14S-GEL	12	11,8	240	150	87	110	1
YT14B-GEL	12	13,7	220	152	71	147	1
YTX14-GEL	12	12	220	152	88	147	1
YT19BL-GEL	12	19	275	182	77	168	0
YTX20CH-GEL	12	18,9	280	150	87	161	1
YTX20L-GEL	12	18,9	300	177	88	156	0

Tuborg AGM YT/YTX/YTZ

Model	Napięcie [V]	Pojemność [Ah]	Prąd rozruchu [A]	Wymiary [mm]			Polaryzacja
				Dł.	Szer.	Wys.	
YTX4L-BS	12	3,2	60	114	71	86	0
YTX5L-BS	12	4,2	100	114	71	106	0
YTX7A-BS	12	6,3	120	151	88	94	1
YTX7L-BS	12	6,3	110	114	71	131	0
YT7B-BS	12	7	110	150	66	94	1
YTZ7S-BS	12	6,3	130	114	71	106	0
YT9A-BS	12	9	140	136	76	139	1
YT9B-BS	12	8,4	120	149	70	105	1
YTX9-BS	12	8,4	150	152	88	106	1
YTX10L-BS	12	10	160	136	91	146	0
YTZ10S-BS	12	9,2	200	151	87	93	0
YT12A-BS	12	10,6	180	150	88	106	1
YT12B-BS	12	10,6	210	151	70	131	1
YTX12-BS	12	10,5	200	152	88	131	1
YT14B-BS	12	12,6	220	152	70	150	1
YTX14-BS	12	12,6	220	152	88	147	1

YTX14AH-BS	12	12	210	136	91	166	1
YTX14AHL-BS	12	12	210	136	91	166	0
YTX14S-BS	12	11,8	240	150	87	110	0
YTX16-BS	12	14,7	240	150	87	161	1
YTX16-BS-1	12	14,7	240	150	87	161	1
YTX20CH-BS	12	18,9	280	150	87	161	1
YTX20L-BS	12	18,9	300	177	88	156	0
YTX24HL-BS	12	22	350	207	92	164	0
YIX30L-BS	12	30	430	168	132	176	0

Tuborg YB z płynnym elektrolitem

Model	Napięcie [V]	Pojemność [Ah]	Prąd rozruchu [A]	Wymiary [mm]			Polaryzacja
				Dł.	Szer.	Wys.	
B38-6A	6	14	130	126	48	126	0
B49-6	6	10,5	100	91	83	161	1
6N11A-3A	6	11,8	110	122	62	131	0
YB4L-B	12	4,2	60	120	70	92	0
YB5L-B	12	5,3	65	120	60	130	0
YB9-B	12	9,5	130	135	75	139	1
YB12A-A	12	12,6	170	134	80	160	1
YB12AL-A2	12	12.6	180	134	80	160	0
YB14L-A2	12	14,7	190	134	89	166	0
HYB16A-A	12	16	210	151	91	180	1